



hp 630 K.../500 TM...  
Packaging machines for clothes and laundry

**hawa**<sup>®</sup>  
2000

hawopack®

hp 630 K.../500 TM...

**Foil-wrapping machines for dry-cleaners,  
laundries, the garment industry, hotels  
and professional packaging companies**



**Wall mounted device  
hp 630 KW, manual  
operation possible**

**Stand device**            **hp 630 KST**

**Wall mounted device** **hp 630 KW**

Cleaned clothes can easily be wrapped (with hangers) in order to prevent them from getting dirty or dusty again. You can determine the length of the package, therefore it is very cheap. Pull over the film, weld-ready packed !



*hp 630 KST stand device with manual operation*

**Technical data:**    **hp 630 KST**

Welding manner:    Impulse separate welding with shoulder form, length 2 x 300 mm  
Film width:            max. 600 mm  
Type of film:         high- low pressure PE-Tube film  
Film thickness:      2 x 0.2 mm  
Device:                with vertical adjustment  
Connection:         230 V / 50 Hz  
Power:                 180 VA  
Dimensions W x D x H: 800 x 580 x 2100 mm  
Weight:                about 48 kg

**hp 630 KW**

Dimensions W x D x H: 800 x 380 x 910 mm  
Weight:                about 40 kg

**Stand device**            **hp 630 KST-BS+SZ**

Bottom sealer, lower welding device with automatic operation via cable pull.



*hp 630 KST-BS stand device, bottom sealer with manual operation*

**Technical data:**

Upper welding device same as hp 630 KST  
**Bottom sealer**  
Welding manner:    Impulse welding seam 3 mm, length 630 mm with vertical adjustment from top welding seam from 450 - 1450 mm  
Device:                with vertical adjustment from top welding seam from 450 - 1450 mm  
Connection:         230 V / 50 Hz  
Power:                 450 VA  
Dimensions W x D x H: 820 x 820 x 2250 mm  
Weight:                about 80 kg

**Stand device**            **hp 630 KST-P**

**Wall mounted device** **hp 630 KW-P**

**Stand device**            **hp 630 KST-P-BS+SZ**

It works by pneumatic safety control with twohand tip-switch. The devices can also be operated manually.



*hp 630 KST-P... stand device with pneumatic operation also with bottom sealer*

**Technical data:** same as hp 630 KST

**Pneumatics:**

Air consumption        max. 0.9 l / cycle  
Connection:            6 bar


**Desktop unit**         **hp 500 TM**

The ideal funnel-welding device for efficient packaging of your goods on the counter. The goods are packaged (clean) hygienic, dustfree and transparent.



**Technical data:**

Film width:            500 mm max.  
Film thickness:        0.2 mm max.  
Welding manner:     separate welding  
Connection:           230 V / 50 Hz  
Power:                 180 VA  
Dimensions W x D x H: 500 x 800 x 400 mm  
Weight:                about 25 kg  
Funnel:                 Chrome steel



## hawopack

Packaging machines for the packaging of clothing and laundry




## hawoplast

Plastic-film welding machines



## hawodent

Film sealing machines and accessories for the packaging of sterile goods



## hawomed

Film sealing machines and accessories for the packaging of sterile goods



## hawotest

Bowie & Dick test system  
Seal-Check



## hawofolie

hawomed-pack tubular films

**hawo**



All references made in this prospect with regard to basic equipment and statutory and legal requirements apply to the Federal Republic of Germany only.

Illustrations may show accessories which are not part of the standard scope of delivery.

Due to continuing improvements, the design and scope of delivery may be subject to change without notice.

Dated November 1999. 9.341.007 Printed in Germany 11/00 / 5.000 / WRB / ST